

## **DECLARATION OF PERFORMANCE**

according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

### **cds-EP-Nivellierschicht**

No. C44000

1. Unique identification code of the product-type:

### **cds-EP-Nivellierschicht**

2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4):

### **Batch no. refer to packaging**

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

### **According to EN 13813: SR – B2,0 – AR1 – IR4**

### **Synthetic resin screed for indoor use**

4. Name, registered trade name or registered trade mark and contact adress of the manufacturer as required under Article 11(5):

**cds Polymere GmbH & Co. KG**  
**Gau-Bickelheimer Straße 72**  
**55576 Sprendlingen /Rhh.**

5. Where applicable, name and contact adress of the authorized representative whose mandate covers the tasks specified in Article 12(2):

### **Not relevant (see 4)**

6. System or systems of assessment and verification of constancy of performance (AVCP) of the construction product as out in CPR, Annex V:

### **System 4 (for indoor use)**

7. In case of the declaration of performance (DoP) concerning a construction product covered by a harmonised standard:

### **Not relevant**

8. In case of the declaration of performance (DoP) concerning a construction product for which a European Technical Assessment (ETA) has been issued:

### **Not relevant**

9. Declared performance:

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Reaction to fire	E <sub>fl</sub> <sup>1)</sup>	System 4	EN 13813:2002
Release of corrosive substances	SR		
Water permeability	NPD		
Wear resistance	≤ AR1		
Bond strength	≥ B2,0		
Impact resistance	≥ IR4		
Sound insulation	NPD		
Sound absorption	NPD		
Thermal resistance	NPD		
Chemical resistance	NPD		

NPD: No Performance Determined


<sup>1)</sup> According to Commission Decision 2010/85/EU of 9th February 2010 the product fulfills the reaction-to-fire performance class E/E<sub>fl</sub> without further testing


10. The performance of the product identified in points 1 and 2 is in conformity with the set of declared performance in point 9. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Oliver Nickel  
Head of Research Development and Quality Control

Sprendlingen, 08.01.2025



	
cds Polymere GmbH & Co. KG Gau-Bickelheimer Straße 72 55576 Sprendlingen/Rhh.	
18	
DoP No. C44000	
EN 13813:2002	
cds-EP-Nivellierschicht	
Synthetic resin screed for indoor use	
Reaction to fire	E <sub>fl</sub>
Release of corrosive substances	SR
Water permeability	NPD
Wear resistance	≤ AR1
Bond strength	≥ B2,0
Impact resistance	≥ IR4
Sound insulation	NPD
Sound absorption	NPD
Thermal resistance	NPD
Chemical resistance	NPD